

MS-920-..

Low Voltage detector and voltage multi-tester DETEX. LCD screen.

Network Type : LV

Application:

- Check the presence of voltage.
- Voltage measurement: up to 690 V AC and 950 V DC.
- Audible continuity test (< 100 Ω).
- Phase pole identification.
- DC polarity identification.
- Phase rotation check (2 lead method).

Features:

- Fitted with IP2X test lead points with retractable trigger tips (MS-920-PG) or retractable sleeves (MS-920 and MS-920-ET). Test lead points Ø 2 mm L: 19 mm (MS-920-EX)
- Three digit colour LCD screen display (red and blue).
- Push-button for the self-test and for the continuity test (100 Ω).
- Indicator light when voltage is dangerous (> 50 V).
- Completely modular and adjustable using type E plugs.
- Lighting feature to light on the working area.



Optional accessories:

- 2 test plug adapters to be fixed on IP2X test lead points with retractable trigger tips enabling to target test plugs Ø 4 mm. Ref. **DX-04**
- Carrying bag with belt loop, Ref. **M-87285**.
- Holder, Ref. M-952325.
- Contact probes for L.V. detectors for installation and sidewalk boxes. Ref. **M-8013**.
- Contact probes for L.V. detectors for flight path. Ref. **M-8014**.
- Hand stick & stick extension. Ref. **M-951143**.

Référence	Dimensions	Frequency	Weight (kg)
	Length (mm)		
MS-920-PG	165	50/60 Hz	0,21
MS-920	165	50/60 Hz	0,21
MS-920-ET	165	50/60 Hz	0,21
MS-920-EX	165	50/60 Hz	0,21